KUNKA
SOUND SYSTEMS

Unique Audio Solutions

IKS18P

PASSIVE SUBWOOFER

IKS18P is a passive subwoofer based on 18" Neodymium speaker that delivers 600W of power. Its small size and low weight makes it an ideal solution for wide variety of situations or a powerful partner to some of our satellite speakers like MAK3P, MAK5P.

PRODUCT DESCRIPTION:

IKS18P is a passive subwoofer that use to be powered by second channel of an active subwoofer IKS18A or any other conventional power amplifier.
It uses "Neutrik" Speakon connection at the back pannel.
It weights only 22 kg and its small size makes it very versatile.

APLICATIONS:

- PA systems.
- Audio-Visual applications.
- Concert Halls.
- Disco-Bars and Discotheques.
- Drum Fill and Side Fill systems.

TECHNICAL SPECIFICATIONS IKS18P





COLORS & PREMIUM FINISHES AVAILABLE

Technical Specifications

GENERAL	
Speaker Handling	600w
Maximum Amplifier Power	1.200w 8 Ohm
Transducers	1x 18" neodymium
Frequency Response	30 Hz – 250 Hz (-3 dB) preset dependent.
Maximun SPL	133 dB (peak)
Coverage	Omni
CROSSOVER	
Frequency	250 hz.
Type	DSP controlled preset speakers
AUDIO OUTPUT	
Connectors	1x Speakon out
Wiring	PIN1+ = CH1+ / PIN1- = CH1- PIN2+ =N.C. / PIN2- = N.C.
HANDLING	
Dimensions (WxHxD)	500 x 500 x 557 mm (19,68 x 19,68 x 21,92 in)
Weight	24 kg / 61,73 lb